

Aluminum Electrolytic Capacitor

HG series

- High ripple current, low impedance at high frequency range.
- 105°C 10000 hours long life .
- RoHS Compliance
- 高紋波電流、高頻低阻抗。
- 105°C 10000小時長壽命產品。

SPECIFICATIONS

Items 項目	Characteristics 特性								
Capacitance Tolerance 靜電容量誤差	± 20%(120Hz,20°C)								
Operating Temperature Range 適用溫度範圍	-40 ~ +105°C								
Rated Voltage Range 額定電壓範圍	6.3 ~ 100VDC								
Leakage Current 洩漏電流	I ≤ 0.01CV or 3 (μA) which is greater.(After 2 minutes application of DC rated voltage, at 20 °C)								
Dissipation Factor 散逸因素(tan δ)	Measurement Frequency: 120Hz. Temperature: 20°C								
	Rated Voltage(V)	6.3	10	16	25	35	50	63	100
	tan δ (Max)	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08
	When nominal capacitance over 1000μF, tanδ shall be added 0.02 to the listed value with increase of every 1000μF.								
Low Temperature Stability 低溫特性 Impedance Ratio(Max) 阻抗比率(最大值)	Measurement Frequency: 120Hz.								
	Rated Voltage(V)	6.3	10	16	25	35	50	63	100
	Z(-25°C)/Z(20°C)	4	3	2	2	2	2	2	2
	Z(-40°C)/Z(20°C)	8	6	4	3	3	3	3	3
Load Life 負荷壽命	Case Size			φ D ≤ 6.3		φ D = 8, 10		φ D ≥ 13	
	Rated Voltage(V)	6.3~10 V		4,000hours		6,000hours		8,000hours	
		16~100 V		5,000hours		7,000hours		10,000hours	
	Capacitance Change	Within ± 25% of Initial Value							
	tan δ	200% or less of Initial Specified Value							
	Leakage Current	Initial Specified Value or less							
Shelf Life 放置壽命	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours 105°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to them 4.1 of JIS C5101-4.								
	Capacitance Change	Within ± 20% of Initial Value							
	tan δ	200% or less of Initial Specified Value							
	Leakage Current	Initial Specified Value or less							
Standards 參照標準	JIS C 5101-4 (IEC 60384)								

Frequency Coefficient of Permissible Ripple Current

Capacitance (μF)	Frequency (Hz)				
	50	120	300	1K	100K
≤ 33	0.50	0.55	0.70	0.90	1.00
47 ~ 330	0.60	0.70	0.85	0.95	1.00
470 ~ 1000	0.65	0.75	0.90	0.98	1.00
1200 ~ 18000	0.70	0.80	0.95	1.00	1.00

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use , the rms ripple current has to be reduced.

Aluminum Electrolytic Capacitor

HG series

STANDARD RATINGS

D×L(mm) ; R.C.(mA rms) at 105°C 100KHz ; IMP (Ω max)at 20°C,-10°C 100KHz.

Cap (μF)	V (Code) Item	16 (1C)			25 (1E)			
		D x L	IMP		R.C.	D x L	IMP	
			20°C	-10°C			20°C	-10°C
47						5x11	0.570	2.300
56		5x11	0.570	2.300	220	5x11	0.570	2.300
100		6.3x11	0.210	0.820	310	6.3x11	0.210	0.870
120		6.3x11	0.210	0.870	340			
220		8x12	0.190	0.850	510	8x12	0.120	0.520
330		8x12	0.120	0.520	650	8x16	0.087	0.350
						10x13	0.081	0.320
470		8x16	0.086	0.350	840	8x20	0.070	0.270
		10x13	0.080	0.320	865	10x16	0.060	0.240
680		8x20	0.069	0.270	1060	10x20	0.045	0.180
		10x16	0.060	0.240	1210	13x16	0.049	0.160
820		10x20	0.052	0.220	1310	10x25	0.041	0.170
1000		10x20	0.045	0.180	1410	10x30	0.030	0.120
						13x21	0.034	0.120
		13x16	0.050	0.160	1450	16x15	0.042	0.120
1200		10x25	0.043	0.170	1650	18x15	0.043	0.110
1500		10x30	0.030	0.120	1920	13x25	0.026	0.089
		13x21	0.035	0.120	1910			
		16x15	0.042	0.120	1940			
1800		13x25	0.028	0.095	2140	13x30	0.024	0.078
						16x22	0.026	0.078
2200		13x25	0.026	0.089	2240	13x35	0.020	0.065
		18x15	0.042	0.110	2220	18x20	0.025	0.066
2700		13x30	0.023	0.077	2650	13x40	0.016	0.056
		16x22	0.026	0.078	2540	16x26	0.021	0.060
3300		13x35	0.020	0.066	2890	16x32	0.016	0.050
						18x25	0.018	0.048
3900		13x40	0.016	0.056	3350	16x36	0.014	0.043
		16x26	0.021	0.060	2930			
		16x22	0.025	0.067	2860	18x32	0.015	0.040
4700		16x32	0.016	0.050	3450	16x40	0.012	0.038
		18x25	0.018	0.049	3150	18x35	0.013	0.040
5600		16x36	0.015	0.044	3620	18x40	0.011	0.032
		18x32	0.015	0.040	4180			
6800		16x40	0.012	0.038	4080			
8200		18x35	0.014	0.038	4230			
10000		18x40	0.011	0.032	4290			

※ 13mm may be replaced by 12.5mm upon customer's request.

Aluminum Electrolytic Capacitor

HG series

STANDARD RATINGS

D×L(mm) ; R.C.(mA rms) at 105°C 100KHz ; IMP (Ω max)at 20°C,-10°C 100KHz.

Cap (μF)	V (Code) Item	35 (1V)			50 (1H)			
		D x L	IMP		R.C.	D x L	IMP	
			20°C	-10°C			20°C	-10°C
22						5x11	0.700	2.800
33		5x11	0.560	2.300	220			
47		6.3x11	0.350	1.400	280	6.3x11	0.380	1.500
56		6.3x11	0.210	0.860	340	6.3x11	0.300	1.200
100		8x12	0.150	0.560	510	8x12	0.160	0.670
120						8x16	0.120	0.480
150		8x12	0.130	0.520	650	10x13	0.120	0.480
180		8x16	0.086	0.350	800	8x20	0.090	0.360
220		8x16	0.086	0.350	850	10x16	0.083	0.340
		10x13	0.080	0.320	865			
270		8x20	0.070	0.260	1060	10x20	0.060	0.240
						13x16	0.062	0.200
330		10x16	0.060	0.240	1210	10x25	0.053	0.220
470		10x20	0.045	0.180	1410	10x30	0.043	0.170
		13x16	0.048	0.150	1460	13x21	0.044	0.150
						16x15	0.054	0.170
560		10x25	0.041	0.160	1650	13x25	0.033	0.110
						18x15	0.053	0.150
680		10x30	0.030	0.120	1920	13x30	0.030	0.100
		13x21	0.033	0.132	1910			
		16x15	0.041	0.143	1950			
820		13x25	0.028	0.088	2100	13x35	0.023	0.081
						16x22	0.033	0.100
1000		13x25	0.028	0.088	2230	13x40	0.020	0.069
						16x26	0.025	0.075
						18x20	0.036	0.097
1200		13x30	0.023	0.078	2660	16x32	0.021	0.066
		16x22	0.026	0.078	2530	18x25	0.025	0.070
1500		13x35	0.020	0.065	2880	16x36	0.018	0.056
1800		13x40	0.016	0.056	3350	16x40	0.016	0.048
		16x26	0.020	0.060	2940			
		18x20	0.025	0.066	2870	18x32	0.021	0.057
2200		16x32	0.016	0.050	3500	18x35	0.017	0.046
		18x25	0.019	0.049	3140			
2700		16x36	0.015	0.044	3620	18x40	0.014	0.038
		18x32	0.014	0.040	4180			
3300		16x40	0.013	0.038	4090			
		18x35	0.014	0.040	4230			
3900		18x40	0.012	0.033	4290			

※ 13mm may be replaced by 12.5mm upon customer's request.

Aluminum Electrolytic Capacitor

HG series

STANDARD RATINGS

D×L(mm) ; R.C.(mA rms) at 105°C 100KHz ; IMP (Ω max)at 20°C,-10°C 100KHz.

Cap (μF)	V (Code) Item	63 (1J)			100 (2A)			
		D x L	IMP		R.C.	D x L	IMP	
			20°C	-10°C			20°C	-10°C
6.8						5x11	2.200	9.200
15		5x11	2.200	9.200	56	6.3x11	1.200	5.000
27						8x12	0.72	3.000
33		6.3x11	1.200	5.000	120			
39						8x16	0.62	2.540
47		8x12	0.680	3.100	190	10x13	0.430	1.800
56		8x12	0.620	2.800	235	8x20	0.320	1.600
68						10x16	0.300	1.500
82		8x16	0.450	2.100	310	10x20	0.210	0.940
		10x13	0.430	1.800	300	13x16	0.230	1.100
100		10x16	0.350	1.800	320	10x25	0.200	0.840
120		8x20	0.330	1.600	362	10x30	0.150	0.710
		10x16	0.300	1.500	357	13x21	0.160	0.640
150						16x15	0.140	0.660
180		10x20	0.200	0.940	470	13x25	0.120	0.450
		13x16	0.230	1.100	465	18x15	0.120	0.500
220		10x25	0.200	0.840	531	13x30	0.110	0.450
						16x22	0.090	0.370
270		10x30	0.150	0.700	663	13x35	0.082	0.350
		13x21	0.160	0.640	690	16x26	0.072	0.270
		16x15	0.130	0.650	795			
330		13x25	0.120	0.450	790	13x40	0.070	0.300
						18x20	0.080	0.300
390		18x15	0.120	0.500	920	16x32	0.053	0.200
						18x25	0.056	0.210
470		13x30	0.100	0.420	910	16x36	0.045	0.170
		16x22	0.090	0.380	1040	18x32	0.047	0.170
560		13x35	0.082	0.350	1050	16x40	0.040	0.150
		16x26	0.073	0.270	1250			
680		13x40	0.070	0.300	1190	18x35	0.040	0.150
		18x20	0.080	0.300	1240			
820		16x32	0.053	0.200	1580	18x40	0.036	0.130
		18x25	0.057	0.210	1490			
1000		16x36	0.045	0.170	1790			
		18x32	0.047	0.170	1640			
1200		16x40	0.039	0.150	2020			
		18x35	0.040	0.150	1790			
1500		18x40	0.035	0.130	2340			

※ 13mm may be replaced by 12.5mm upon customer's request.